

# Raimond R127-R163-R199

RAIMOND PUTS | REALISATION BY OX-ID



The Raimond light is a perfect sphere of mathematical ingredients punctuated by tiny LED lights. It is specially detailed to spread warm white light in every direction and looking at the light feels like staring into the soft glow of a starry night. Inspired by the geodesic dome, designed by Buckminster Fuller, the Raimond lights are the result of almost forty years of research and dedication of mechanical engineer and self-taught designer Raimond Puts (1937 – 2012).

---

## *Detailing*



A double-shell sphere made with stainless steel strips, forming a thin and openwork triangular mesh that transport the electric current.


---

## *Colours*

Stainless steel

# Raimond R127-R163-R199 / R127

## Dimensions



## Product

**WIDTH** 127cm | 50"  
**HEIGHT** 127cm | 50"  
**DEPTH** 127cm | 50"  
**DIAMETER** 127cm | 50"  
**WEIGHT NETTO** 4.5kg | 9.92lbs

## Packaging

**WIDTH** 150cm | 59.1"  
**HEIGHT** 150cm | 59.1"  
**CUBAGE** 3.38m<sup>3</sup> | 119.19ft<sup>3</sup>  
**LENGTH** 150cm | 59.1"  
**WEIGHT** 80.5kg | 177.47lbs

## Technical CE

### MATERIAL

Stainless Steel Sphere with PMMA lenses

### ENERGY LABEL

Energy Label B

### LIGHTSOURCE TYPE

LED

### NUMBER OF LIGHTSOURCES

492

### INPUT VOLTAGE

110-240

### MAX POWER CONSUMPTION

46W

### LAMPHOLDER

LED (Solid state)

### CABLE COLOUR

Transparent with tinned cores

### COLOUR TEMPERATUE

2700 K

### LIGHT DIRECTION

All directions

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE INCLUDED

Yes

### SHAPE

Globe

### FREQUENCY

50/60

### DIMMABLE

Yes

### LIFETIME

50000 hours

### CABLE LENGTH

1000cm | 393.7"

### CRI

71

### LIGHT OUTPUT

1684 lm

## Technical CU

**MATERIAL**

Stainless Steel Sphere with PMMA lenses

**ENERGY LABEL**

Energy Label B

**LIGHTSOURCE TYPE**

LED

**NUMBER OF LIGHTSOURCES**

492

**INPUT VOLTAGE**

110-240

**MAX POWER CONSUMPTION**

46W

**LAMPHOLDER**

LED (Solid state)

**CABLE COLOUR**

Transparent with tinned cores

**COLOUR TEMPERATUE**

2700 K

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE INCLUDED**

Yes

**SHAPE**

Globe

**FREQUENCY**

50/60

**DIMMABLE**

Yes

**LIFETIME**

50000 hours

**CABLE LENGTH**


1000cm | 393.7"

**CRI**

72

**LIGHT OUTPUT**

1684 lm

*Raimond R127-R163-R199 / R163**Dimensions**Product***WIDTH** 163cm | 64.2"**HEIGHT** 163cm | 64.2"**DEPTH** 163cm | 64.2"**DIAMETER** 163cm | 64.2"**WEIGHT NETTO** 7.5kg |

16.53lbs

*Packaging***WIDTH** 185cm | 72.8"**HEIGHT** 185cm | 72.8"**CUBAGE** 6.33m<sup>3</sup> | 223.6ft<sup>3</sup>**LENGTH** 185cm | 72.8"**WEIGHT** 117.5kg | 259.04lbs*Technical CE***MATERIAL**

Stainless Steel Sphere with PMMA lenses

**ENERGY LABEL**

Energy Label B

**LIGHTSOURCE TYPE**

LED

**NUMBER OF LIGHTSOURCES**

812

**INPUT VOLTAGE**

110-240

**MAX POWER CONSUMPTION**

70W

**LAMPHOLDER**

LED (Solid state)

**CABLE COLOUR**

Transparent with tinned cores

**COLOUR TEMPERATUE**

2700 K

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE INCLUDED**

Yes

**SHAPE**

Globe

**FREQUENCY**

50/60

**DIMMABLE**

Yes

**LIFETIME**

50000 hours

**CABLE LENGTH**

1000cm | 393.7"

**CRI**

71

**LIGHT OUTPUT**

2779 lm

---

*Technical CU***MATERIAL**

Stainless Steel Sphere with PMMA lenses

**ENERGY LABEL**

Energy Label B

**LIGHTSOURCE TYPE**

LED

**NUMBER OF LIGHTSOURCES**

812

**INPUT VOLTAGE**

110-240

**MAX POWER CONSUMPTION**

70W

**LAMPHOLDER**

LED (Solid state)

**CABLE COLOUR**

Transparent with tinned cores

**COLOUR TEMPERATUE**

2700 K

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE INCLUDED**

Yes

**SHAPE**

Globe

**FREQUENCY**

50/60

**DIMMABLE**

Yes

**LIFETIME**

50000 hours

**CABLE LENGTH**

1000cm | 393.7"

**CRI**


71

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

2779 lm

*Raimond R127-R163-R199 / R199**Dimensions**Product*

**WIDTH** 199cm | 78.3"  
**HEIGHT** 199cm | 78.3"  
**DEPTH** 199cm | 78.3"  
**DIAMETER** 199cm | 78.3"  
**WEIGHT NETTO** 12.5kg | 27.56lbs

*Packaging*

**WIDTH** 220cm | 86.6"  
**HEIGHT** 220cm | 86.6"  
**CUBAGE** 10.65m<sup>3</sup> | 376.03ft<sup>3</sup>  
**LENGTH** 220cm | 86.6"  
**WEIGHT** 120kg | 264.55lbs

*Technical CE***MATERIAL**

Stainless Steel Sphere with PMMA lenses

**ENERGY LABEL**

Energy Label B

**LIGHTSOURCE TYPE**

LED

**NUMBER OF LIGHTSOURCES**

1212

**INPUT VOLTAGE**

110-240

**MAX POWER CONSUMPTION**

100W

**LAMPHOLDER**

LED (Solid state)

**CABLE COLOUR**

Transparent with tinned cores

**COLOUR TEMPERATUE**

2700 K

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE INCLUDED**

Yes

**SHAPE**

Globe

**FREQUENCY**

50/60

**DIMMABLE**

Yes

**LIFETIME**

50000 hours

**CABLE LENGTH**

1000cm | 393.7"

**CRI**

71

**LIGHT OUTPUT**

4148 lm

## Technical CU

### MATERIAL

Stainless Steel Sphere with PMMA lenses

### ENERGY LABEL

Energy Label B

### LIGHTSOURCE TYPE

LED

### NUMBER OF LIGHTSOURCES

1212

### INPUT VOLTAGE

110-240

### MAX POWER CONSUMPTION

100W

### LAMPHOLDER

LED (Solid state)

### CABLE COLOUR

Transparent with tinned cores

### COLOUR TEMPERATUE

2700 K

### LIGHT DIRECTION

All directions

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE INCLUDED

Yes

### SHAPE

Globe

### FREQUENCY

50/60

### DIMMABLE

Yes

### LIFETIME

50000 hours

### CABLE LENGTH

1000cm | 393.7"

### CRI

71

### LIGHT OUTPUT

4148 lm

---

## Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

### DIMMER TYPE

Dimmable power supply available upon request