

General

| | |
|---------------------------|--|
| Location: | Interior |
| Class: | CE (Class I) |
| IP-rating: | IP20 |
| Driver included: | Yes |
| Installation orientation: | Ceiling mount |
| Main material: | Aluminium powder coated RAL9016 |
| Dimensions (mm): | H: 300mm W: 190mm D: 40mm |
| Cut out hole (mm): | - |
| Recess depth (mm): | - |
| Lamp included: | Yes |
| Dimmable: | Yes |
| Dimming method: | Mains dimmable (See catalog for other options) |

Models



CODE WL04 0101 LED (*)

White Line AR48 duo
2700K - CRI>97
2xLED 4W - 800lm - 350mA



CODE WL04 0101 LEDH (*)

White Line AR48 duo - high ring
2700K - CRI>97
2xLED 4W - 800lm - 350mA



CODE WL04 0101 LEDDTW (*)

White Line AR48 duo - dim to warm
2800K-1800K - CRI>95
2xLED 4W - 960lm - 250mA



CODE WL04 0101 LEDHDTW (*)

White Line AR48 duo - high ring - dim to warm
2800K-1800K - CRI>95
2xLED 4W - 960lm - 250mA

Required options (*)

| | |
|-------------------------|-----------------------|
| WL H40 REFLECTOR | Spot 19° or Flood 34° |
|-------------------------|-----------------------|