

	technics	In case of precast concrete panels, gear inclusive.	In case of finished concrete ceiling, gear exclusive.	Name	Reference	Lamp type	A	B	C	D	∅E	
							□ 91	320	320	200	200	
1	cut out			Concrete plasterkit down 80	KR747702	QR-CBC51	□ 91	320	320	200	200	
						LED dir (Kr94773x)	□ 91	300	300	157	170	
						LED dir (Kr94793x)	□ 91	344	344	120	390	
						Fixed, WW (Kr94703x, Kr94743x)	□ 91	260	260	100	250	
						Audio	□ 91	200	200	130	150	
						Concrete plasterkit down 165	KR747712	QT12-ax	□ 287	300	300	200
								QR-LP111/LED-LP111	□ 287	300	300	230
								HIT-TC	□ 287	300	300	230
								HIR-CE111	□ 287	300	300	230
								QT12-ax WW	□ 287	300	300	175
								HIT-TC WW	□ 287	300	300	205
								LED wallwasher	□ 287	300	300	200
				LED	□ 287	300	300	200				

	2	dimensions	Down 80		Down 165	
			430	410	348	324
1	cut out					
2	cut out					

	3	installation	Reinforce perfo plate with gypsum plate or wooden plate to avoid bending.		
			Down 80	Down 165	Down 165
1	cut out				
2	cut out				

	4	installation	Put the plasterkit through the hole.		
			Down 80	Down 165	Down 165
1	cut out				
2	cut out				

	4	installation	Fix the plasterkit with screws.			Fill around perimeter of plasterkit using suitable filler and plaster to hide screws and plasterkit.			For installing Down 80 and 165, see the corresponding installation manual.		
			Down 80	Down 165	Down 165	Down 80	Down 165	Down 165	Down 80	Down 165	Down 165
1	cut out										
2	cut out										