

MUSA

Design by Note Design Studio.

VIBIA

Reference

7402.

Application

Table Lamps

Installation type

Surface

Description

Vibia offers a table lamp. The aluminum base captures the light as the small glass sphere and transforms it into a soft illumination.

Diffuser

Mat opal triplex blown-glass diffuser

Materials

Body: Aluminum

Diffuser: Blown-glass

Finish



7402-58 Matt salmon lacquer (NCS S 1010-Y50R)




7402-59 Mink (NCS S 2005-Y50R)



7402-93 White (RAL 9016)


Sketch



Electrical characteristics

1 x LED 4,5W 350mA

Total 4.5 W



Light source: 2700K CRI >90 449 lm 99 lm/W

Fixture: 317.66 lm 51.75 lm/W

Driver included: CV - Contant Voltage 100-240V 50/60Hz

Electronic dimming Push

Technical characteristics

- Switch on the base

Physical characteristics

1 Box / 0.17 x 0.32 x 0.30 m. / Vol. 0.0163 m³ /

Gross weight 1.3 kg. / Net weight 0.9 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 317.66 lm

Maximum value : 206.01 cd/klm

Light position : C=75.00 G=155.00

Symmetry on the planes : Symmetrical planes

270-90

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates

