

TEMPO

Design by Lieve Altherr.

Reference

5776.

Application

Hanging lamps

Installation type

Surface

Description

Tempo pendant lamps are a design by Lieve Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blow-glass diffuser

Materials

LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

Finish



5776-18 Graphite (ADAPTA RF 9913 WX)



5776-35 Brick (NCS S 4040-Y70R)




5776-58 Cream (RAL 7044)



5776-62 Green (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA



Light source: 2700K CRI >90 440.81 lm 110 lm/W

Fixture: 317.77 lm 79.44 lm/W

Driver included: CC - Constant Current 350 mA 110-240V 50/60Hz

Electronic dimming 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional DALI or Casambi

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0429 m³ /

Gross weight 5.5 kg. / Net weight 4.0 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 57.61 lm/W

Coordinate system : CG

Total flux : 317.77 lm

Maximum value : 315.71 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates

